

#OVERVIEW

SELVE Drives

Use, Functions and Specifications



	SE Pro	SEE	SEE-NHK	SE Plus	SEZ	SEM Plus	SP	SP Rescue	SP-NHK
Use	Roller shutter	X	X	X	X		X	X	X
	Screen				X		X		
	Zip-screen				X	X	X		
	Folding arm awning			X		X	X		
Technical execution	Wired version	X	X	X	X	X	X	X	X
	Radio version (-RC) available	X	X		X	X			
	Integrated SMI technology available	X			X	X			
	Series 1 (SW 40, for shafts from Ø 40)	X	X		X	X		X	
	Series 2 (SW 50 + 60, for shafts from Ø 50)	X	X	X	X	X	X	X	X
	Series 3 (SW 70, for shafts from Ø 70)				X		X		X
	Short version available	X	X			X		X	X
	Fast rotation speed 28 rpm available				X	X		X	
	Round motor head available				X				
Functions	Mechanical limit stop						X	X	X
	Electrical limit stop	X	X	X	X	X			
	Plug & Play setting		X	X					
	Automatic setting of the end limit positions	X	X	X		X			
	Manual setting of the end limit positions	X	X		X	X	X	X	X
	Additional intermediate and ventilation position (-RC)	X	X		X	X	X		
	Obstacle detection with reversion	X (soft)	X			X (soft, 3x)			
	Learning overload protection / freeze up protection	X	X	X	X	X	X		
	Wind gust detection					X			
	Relief of the upper end limit position	X	X	X	X	X	X (deact.)		
	Use with burglar-proof fixations / blocking springs only		X	X					
	Use with burglar-proof fixations / blocking springs possible	X (manually)	X	X	X			X	X
	Automatic direction assignment	X			X	X	X		
	Parallel connection possible	X	X	X	X	X	X		
	Emergency operation in case of power failure			X					X
	Use at second emergency escape route			X (crank)					X
Plugable cable (series 2)	X	X		X	X	X	X		
VDE sign (series 2, 7–30 Nm, also -RC)	X	X		X	X	X	X		